

FOUR SPIRAL - 4SP HOSE



4 SP

Tube: Oil resistant synthetic rubber

Reinforcement: Four high tensile steel wire spirals

Cover: Abrasion, ozone and hydrocarbon resistant synthetic rubber

Application: Very high pressure hydraulic lines, fuel oil, air & water

Temp : - 40°C to + 100°C

Catalog No.	I.D. mm	Working Pressure Kg/cm ²	Test Pressure Kg/cm ²	Burst Pressure Kg/cm ²	Minimum Bend Radius mm
SP4-04	6.4	460	920	1840	150
SP4-06	9.5	453	906	1812	180
SP4-08	12.7	421	842	1684	230
SP4-10	15.9	351	702	1404	250
SP4-12	19.0	351	702	1404	300
SP4-16	25.4	281	562	1124	340

FOUR SPIRAL - 4SH HOSE



4 SH

Tube: Oil resistant synthetic rubber

Reinforcement: Four high tensile steel wire spirals

Cover: Abrasion, ozone and hydrocarbon resistant synthetic rubber

Application: Very high pressure hydraulic lines, fuel oil, air & water

Temp : - 40 °c to + 100°C

SH4-12	19.0	421	842	1684	280
SH4-16	25.4	386	772	1544	340
SH4-20	31.8	330	660	1320	460
SH4-24	38.1	295	590	1180	560
SH4-32	50.8	256	512	1024	700