

## THERMOPLASTIC HIGH PRESSURE HOSE



### TP-7 Confirming to SAE 100 R7

**Tube:** Thermoplastic techno polymer / polyamide

**Reinforcement:** Single braid of high tensile synthetic fibre.

**Cover:** Polyurethane

Temp : - 40°C to + 100°C

Catalog No.	I.D. mm	Working Pressure Kg/cm <sup>2</sup>	Test Pressure Kg/cm <sup>2</sup>	Burst Pressure Kg/cm <sup>2</sup>	Minimum Bend Radius mm
TP7-03	4.8	208	416	832	75
TP7-04	6.4	190	380	759	102
TP7-05	8.0	172	344	690	114
TP7-06	9.5	155	310	621	127
TP7-08	12.7	138	276	552	178
TP7-10	16.0	103	206	414	203
TP7-12	19.0	86	172	345	254
TP7-16	24.4	69	138	276	305

## THERMOPLASTIC HIGH PRESSURE HOSE



### TP-8 Confirming to SAE 100 R8

**Tube:** Thermoplastic techno polymer / polyamide.

**Reinforcement:** Double braid of high tensile synthetic fibre.

**Cover:** Polyurethane.

Temp : - 40°C to + 100°C

TP8-04	6.4	345	690	1379	102
TP8-05	8.0	293	586	1172	114
TP8-06	9.5	276	552	1103	127
TP8-08	12.7	241	482	966	178
TP8-10	16.0	190	380	759	203
TP8-12	19.0	155	310	621	240
TP8-16	24.4	138	276	552	305